





ST 224

Husqvarna ST 224 has been developed for homeowners who need a high-performing snow blower to clear snow from large garage driveways and paths. It works regardless of surface type thanks to the adjustable skid shoes. Husqvarna ST 224 has been designed for occasional use in all snow conditions. It has an efficient two-stage system with high throwing capacity. The handle has adjustable height for comfortable use. Friction-disc transmission ensures smooth operation. Features heated handle grips, LED headlights and electric starter for work in all weather conditions.



TWO-STAGE SYSTEM

Snow is fed into the housing by an auger and then discharged through the chute by an impeller.



HANDLE HEIGHT ADJUSTMENT

Adjustable handle height for improved ergonomics.



RIBBON AUGER

The ribbon auger mixes air into the snow, which makes the snow easy to handle and thereby ensures efficient clearing.



ELECTRIC STARTER

Connect to a power outlet and start the engine by pressing a button. Our starter system ensures that you'll never have to worry about a dead battery.

Features

- Friction disc transmission for easy speed changes
- LED headlight/s for operation in dark conditions
- Heated handle grips for comfortable operation
- Differential lock for optimum traction
- Heavy-tread tires for extra good traction
- Plastic skid shoes for merciful treatment of delicate grounds
- Adjustable skid shoes for protection of ground
- Robust auger housing for sturdy operation
- Aluminium auger gearbox
- High speed impeller for long throwing distance
- Control for horizontal throwing direction
- Control for vertical throwing direction
- Interlock handle for single hand control
- Loop handle for optimum grip and control
- Clearing stick for chute
- Husqvarna brand engine with 5-year warranty
- Quiet muffler for user comfort
- Throttle control for easy idling down
- Durable control cables of premium quality
- Pin-lock wheels for tool-less shifting

Technical data

Blower type	Two-stage
Working width	24 inch
Auger diameter	30.5 cm / 12"
Number of impeller blades	3
Engine manufacturer	LCT
Cylinder displacement	208 cc
Net power at preset rpm	4.7 kW @ 3600 rpm
Horsepower	6.3 hp / 4.7 kW
Gross Torque	9.5 lb-ft
Fuel tank volume (with reserve)	0.69 gal.
Transmission type	Friction Disc
Transmission steps forward	6
Transmission steps reverse	1
Tire size	380 mm / 15"
Handle height adjustment	4 steps
Base machine, length	58.5 inch
Base machine, width	24 inch
Base machine, height	40.5 inch
Weight	198.6 lbs
Sound pressure level at operators ear	88.4 dB(A)
Sound power level, measured	99 dB(A)
Sound power level, guaranteed (LWA)	105 dB(A)
Vibrations handles	5.74 m/s ²

ARTICLES

961 93 00-96 ST 224 \$ 799.95

