



Husqvarna®



445

New powerful all-round saw for people who value professional qualities in a saw. The X-Torq® engine means lower fuel consumption and reduced emission levels. Auto return stop switch and visible fuel level makes the saw easier to handle. Equipped with Smart Start® and fuel pump to ensure easy starts every time.



AIR INJECTION

Centrifugal air cleaning system removes larger dust and debris particles before reaching the air filter. This results in reduced air filter cleanings and improved engine life.



X-TORQ®

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



EASY TO START

Combined start/stop switch and fuel pump make the saw very easy to start.



QUICK-RELEASE AIR FILTER

Facilitates cleaning and replacement of the air filter.

Features

- Felling marks for correct felling direction
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Easy to maintain with snap locked cylinder cover
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands
- Fuel level window
- Easy to start
- Smart Start® for easy starting
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	45.7 cc
Power output	2.8 hp
Maximum power speed	9000 rpm
Fuel tank volume	15.22 fl oz
Fuel consumption	481 g/kWh
Idling speed	2700 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.02"
Torque, max.	2.4 Nm/6300 rpm
Oil tank volume	0.55 US pint
Oil pump type	Fixed flow
Equivalent vibration level (ahv, eq) front/rear handle	1.9/2.6 m/s ²
Sound pressure level at operators ear	103 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Chain pitch	.325"
Chain speed at 133% of maximum engine power speed	75.46 fts
Recommended bar length, min-max	13"-20"
Weight (excl. cutting equipment)	10.8 lbs

ARTICLES

966 95 53-36	16" Bar, .325" Pitch, .050" Gauge, Assembly Required	\$ 329.95
966 90 66-36	16" Bar, .325" Pitch, .050" Gauge, Fully Assembled	\$ 329.95
966 95 53-38	18" Bar, .325" Pitch, .050" Gauge, Assembly Required	\$ 339.95
965 08 40-01	18" Bar, .325" Pitch, .050" Gauge, Fully Assembled	\$ 339.95

