

1632 OPEN END BELT SANDER, 5HP 1PH 230V

1791250

The 16" Open-End Sander has front mounted controls and a load meter, which maintains a constant check during operation. Metal-tipped safety limiters inside the machine will stop the sander immediately should belt breakage occur. The combination head means a more consistent finish, and pneumatic conveyor belt tracking keeps belts automatically centered.

[BUY NOW](#)

[WHERE TO BUY](#)



FEATURES

- The combination head promotes a more consistent finish
- Pneumatic sanding belt tracking keeps belt centered
- Conveniently mounted load meter maintains constant check during operation
- Limiters will stop sander instantly if belt breakage occurs
- Side access door for easy belt changes
- Standard Equipment:
- 5HP motor
- Emergency rail stop
- Emergency stop button
- Dust collection port
- 17" x 54" sanding belt

SPECIFICATIONS

Style (Type)	Open End Belt
Maximum Board Width (In.)	16 (32)
Maximum Board Thickness (In.)	5
Minimum Board Length (In.)	13-3/4
Feed Rate (FPM)	15/32.5
Sanding Belt Speed (FPM)	2,200
Sanding Belt Size (In.)	17 x 54
Air Required	yes
Dust Collection Minimum CFM Required (CFM)	800
Dust Port Outside Diameter (In.)	4
Feed Motor Power (HP)	1/4
Motor Power (HP)	5
Motor Phase	1
Motor Voltage (V.)	230 only
Recommended Circuit Size (Amps.)	40

RESOURCES

- [Manual](#)
- [View More Details](#)