

# WGen7500DF



## 7500 Watt Open Frame Dual Fuel (Gas/LPG) Portable Generator

Gas: 7500W Running 9500W Peak | Propane: 6750W Running 8550W Peak

Rugged roll bars for added strength and protection

Fuel gauge on top of 6.6 gal. gas tank



Push button electric start, lights up green when unit is on

Fuel selector switch allows to easily switch from gas to propane without shutting off the unit

Battery charging port (charger included)

Dependable 13 HP 420cc OHV 4-Stroke Westinghouse engine

Remote start key fob included for starting and stopping generator up to 109 yards away

Propane hook up (LPG hose included)



120V 20A GFCI OUTLETS

FUEL SELECTOR SWITCH

ONE TOUCH PUSH BUTTON START

120/240V 30A TWIST LOCK OUTLET

ENGINE SHUT OFF



TWO USB PORTS

WESTINGHOUSE ST SWITCH OUTLET

VFT METER  
BATTERY CHARGING PORT

20A BREAKERS

### What Comes in the Box



# WGen7500DF



Gasoline Running Watts	7500
Gasoline Peak Watts	9500
Gasoline Running Amps	31 amps
Gasoline Peak Amps	39 amps
Propane Running Watts	6750
Propane Peak Watts	8550
Propane Running Amps	28 amps
Propane Peak Amps	35.6 amps
AC Voltage	120/240 Volts
AC Frequency	60 Hz
Engine Horse Power (HP)	13 HP
Total Harmonic Distortion (THD)	<23%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Electric, Remote, Recoil
Battery	Yes
Battery Charger Included	Yes
Remote Start Fob Included	Yes (factory paired)
Remote Start Distance (yards/meters)	109 yd. (100 m.)
Push Button Start	Yes
Mobile App Compatible	No
Engine Displacement	420cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume (dBA)	74 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140546
DF Regulator Assembly (sold separate)	140547
Auto Idle Control	No
Built-in Inverter	No
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt. (37.2 oz.)
Oil Capacity (Quarts/Ounces)	1.1 qt. (37.2 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Propane, Unleaded Gasoline, %10 Ethanol or less

Fuel Shut Off	Manual
Fuel Tank Capacity (Gallons/Liters)	6.6 gal. (25 L)
Gas - Run Time at %25 Load (hrs.)	16 hrs.
Gas - Run Time at %50 Load (hrs.)	11 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Automatic
Choke Location	Above Air Filter
AC Outlets	(1) 120/240V 30A (L14-30R) (2) Duplex 120V 20A GFCI (5-20R)
DC Outlets	(2) 5V USB Ports
Ground	Neutral Bonded
Covered Outlets	Yes
Transfer Switch Ready	Yes
Westinghouse Portable Transfer Switch Ready (ST Switch)	Yes
GFCI Outlets	Yes
VFT Data Center (volts, frequency, lifetime hours)	Yes
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single Handle with Foam Grip
Wheel Kit Included	Yes
Wheel Size	10 in. Diameter, 2.5 in. Wide
Wheel Type	Polyurethane
Frame Thickness in. (mm)	1.25 in. (25 mm)
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs
Commercial Warranty	6 Months or 1000 hrs
Assembled Length in. (mm)	27.2 in. (690.8 mm)
Assembled Width in. (mm)	26.1 in. (662.94 mm)
Assembled Height in. (mm)	26 in. (660.4 mm)
Extended Length in. (mm)	40.7 in. (1033.9 mm)
Carton Length in. (mm)	31.1 in. (790 mm)
Carton Width in. (mm)	22.4 in. (570 mm)
Carton Height in. (mm)	23.2 in. (590 mm)
Dry Unit Weight lb. (kg)	194 lb. (88 kg)
Shipping Weight lb. (kg)	202 lb. (91.6 kg)
UPC	855464003636
GTIN	00855464003636

09252017KD

©2017 Westinghouse Portable Power

Specifications are subject to change without notice

Westinghouse Portable Power

777 Manor Park Dr., Columbus, OH 43228

