

Take advantage of remarkable power and performance at a great value with a Sno-Tek six-speed, two-stage snow thrower. Featuring a rugged 208cc Sno-Tek engine, remote chute deflector, and a 24-inch wide housing, you'll be prepared for treacherous winter conditions.

**Convenient levers** allow for one-handed operation leaving the other free to reposition the chute without stopping.

**Remote chute deflector** allows the operator to easily control the height of the snow plume.

**Rugged all-steel dash** panel and controls withstand the elements.

**Powerful 9.5 ft/lb, 208cc Sno-Tek engine.**

**Polymer chute** with 2.5X Quick Turn and 205-degree rotation stands up to the wear and tear caused by packed snow, ice, and debris.

**120V Electric Start** and recoil backup for smooth startup in adverse conditions.

**A robust freeze-resistant 12-inch, 3-blade, high-speed impeller** throws snow fast and far for quick, efficient snow removal.

**Serrated steel augers** relentlessly work through packed snow and ice pulling it into a powerful impeller.

**Pin-lock axle** provides maneuverability when unlocked, or maximum traction when locked.

**Aggressive Polar Trac tires** provide traction to overcome slippery conditions.

**Top-Load aluminum gear case** with alloy steel gears and synthetic gear oil ensures long-life.

**24-inch wide housing** captures more snow for quick, efficient snow removal.



# SPECIFICATIONS

# Must have accessories



## DESIGNATION

**SNO-TEK  
24**

MODEL #	920402
STAGE TYPE	Two-Stage
ENGINE*	208cc Sno-Tek
STARTING SYSTEM	120V/Recoil
CLEARING WIDTH	24 in (60.1 cm)
HOUSING HEIGHT	20 in (50.8 cm)
THROWING DISTANCE	3 ft - 40 ft (1.9-12.2 m)
CHUTE TURNING RADIUS	205°
CHUTE ROTATION	2.5x Quick Turn
CHUTE CONSTRUCTION	Polymer
DEFLECTOR CONTROL	Remote
ONE HAND INTERLOCK	Standard
TIRE SIZE	13 in X 4 in (33 x 10 cm)
TIRE TYPE	Polar Trac
AXLE SYSTEM	Pin Lock
FUEL TANK CAPACITY	2.9qt (2.7L)
DRIVE TYPE	Disc-O-Matic
SPEEDS	6 Forward/2 Reverse
GEAR CASE	Top Load Aluminum
IMPELLER PROFILE	Steel 3 Blade
IMPELLER DIAMETER	12 in (30.5 cm)
AUGER DIAMETER	11 in (27.9 cm)
AUGER TYPE	Steel Serrated
SKID SHOES	Steel Reversible

## DIMENSIONS:

LENGTH	44.75 in (113.67 cm)
WIDTH	30.13 in (76.52 cm)
HEIGHT	31.5 in (80.01 cm)
WEIGHT	204 lbs (92.53 kg)

## WARRANTY:

2-year Limited Consumer,  
90 day Limited Commercial



### Snow Thrower Cover

Ideal for in-between snow and off-season storage, our snow thrower cover is water repellent and tear-resistant for long-lasting protection.



### Floor Mat

Heavy-duty floor mat collects water from melting snow providing a protective layer between the machine and floor surface during storage.



### Tire Chains

Featuring superior two-link spaced cross chains, our tire chains provide added traction for safety on hills, ice and hard-packed snow.



### Non-Abrasive Skid Shoes

Steel or polyethylene replacement skid shoes prolong the life of the unit.

An *Ariens* Company Brand

\* Engine output stated in gross torque per SAE J1940 as rated by engine manufacturer. Sno-Tek unit features and specifications are subject to change without notice. ©2015 Ariens Company ® Registered Trademark and ™ Trademark of Ariens Company. LCT is a registered Trademark of its respective company.

For a complete listing of compatible attachments and accessories, visit your local Sno-Tek® dealer or go to: [sno-tek.net](http://sno-tek.net).